





1 1/2" TIE-BACK ADAPTER U-SHAPED FOR 1 1/2" ROD



NOTES:

1. PLATE TO MEET OR EXCEED REQUIREMENTS OF ASTM A572, GRADE 50.
2. ULTIMATE CAPACITY OF U-SHAPED UNIT IS 60 KIPS. TO OBTAIN FULL CAPACITY, BOLT MUST BE TIGHTENED UNTIL WALLS OF ADAPTER ARE TIGHT TO THE HELICAL SHAFT. THREADED ROD MAY LIMIT CAPACITY OF THE ASSEMBLY.
3. GALVANIZING PER ASTM A153/ASTM A123. BARE STEEL IS ALSO AVAILABLE.
4. (1) 3/4" DIAMETER 5" LONG GALVANIZED HEAVY HEX BOLT ASTM A325 AND (1) 3/4" GALVANIZED HEX NUT (GRADE A) TO BE INCLUDED.
5. THREADED ROD AND NUTS/WASHERS ARE NOT INCLUDED. THEY CAN BE PURCHASED SEPARATELY FROM IDEAL.

DRAWN AP	4/24/2020
CHECKED DSS	4/27/2020

IDEAL MANUFACTURING, INC.
999 PICTURE PARKWAY
WEBSTER, NY 14580
800-789-4810 | WWW.IDL-GRP.COM



IDEAL
Group

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
IDEAL MANUFACTURING, INC. ANY
REPRODUCTION IN PART OR AS A
WHOLE WITHOUT WRITTEN
PERMISSION OF IDEAL
MANUFACTURING, INC. IS PROHIBITED.

NOT TO SCALE ALL UNITS IN INCHES U.N.O.	SIZE A	DWG NO SQ150TBAU112G	REV 0	SHEET 1 OF 1
--	-----------	-------------------------	----------	--------------