


HELICAL PILE SUPPORTED WALKWAY

NOTES:

- 1. THIS DRAWING IS ONLY A SUGGESTION FOR DESIGN AND CONSTRUCTION. THE ACTUAL DESIGN IS TO BE PERFORMED BY A REGISTERED PROFESSIONAL ENGINEER.
- 2. THE HELICAL PILE DEPTH AND HELIX CONFIGURATION WILL DEPEND ON SITE SPECIFIC SOIL CONDITIONS.
- 3. VERTICAL HELICAL PILES ARE TYPICALLY 2 7/8" O.D. ROUND SHAFT FOR BOARDWALK APPLICATION.
- 4. BATTERED HELICAL PILES ARE TYPICALLY 1 1/2" ROUND CORNER SQUARE SHAFT FOR BOARDWALK APPLICATIONS.
- 5. HEIGHT ABOVE GRADE IS TYPICALLY LESS THAN 3'-0". CONSULT A REGISTERED PROFESSIONAL ENGINEER IF THAT HEIGHT WILL BE EXCEEDED.



DRAWN AP	4/17/2020
CHECKED LRS	4/20/2020
IDEAL MANUFACTURING, INC. 999 PICTURE PARKWAY WEBSTER, NY 14580 800-789-4810 WWW.IDL-GRP.COM	
NOT TO SCALE ALL UNITS IN INCHES U.N.O.	



PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF IDEAL MANUFACTURING, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT WRITTEN PERMISSION OF IDEAL MANUFACTURING, INC. IS PROHIBITED.	
SIZE B	DWG NO Helical Pile Supported Walkway
REV 0	SHEET 1 OF 1